

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Roiter Srl
Address	Via Achille Grandi 5, Rovigo, 45100, Italy
Type	Flexible Hoses
Description	Rubber Hose
Trade Name	Type: S10, S15, L15
Application	Marine, Offshore and Industrial
Specified Standard	UNI EN 1765:2016 LR Rules and Regulations for the Classification of Ships

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Fabrizio Cadenaro

Lead Technical Specialist - Alternative Fuels
to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.

Type Approval Certificate

Ratings

Type L15:

Size: 2" (51 mm), 3" (76 mm), 4" (102 mm), 6" (152 mm), 8" (203 mm)
Maximum working pressure = 15 bar
Temperature range: -40°C /+ 100°C

Type S15:

Size: 4" (102 mm), 6" (152 mm), 8" (203 mm), 10" (254 mm), 12" (305 mm),
14" (355 mm), 16" (405 mm), 20" (500 mm)
Maximum working pressure = 15 bar
Temperature range: -40°C /+ 100°C

Type S10:

Size: 4" (102 mm), 6" (152 mm), 8" (203 mm), 10" (254 mm), 12" (305 mm),
14" (355 mm), 16" (405 mm)
Maximum working pressure = 10 bar
Temperature range: -40°C /+ 100°C

Other Conditions

The Manufacturer Roiter Srl is a member of Matec Group Srl

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

The Design Appraisal Document LR2275253DA and its supplementary Type Approval Terms and Conditions form part of this Certificate.