

# MPH HOSE - MULTIPURPOSE

# FARIVO®



Application:	Multi-purpose rubber hose, used in refineries, shipyards, steel mills, foundries, auto plants and construction industries. For conveying a wide range of media including air, water, nitrogen, oil and other petroleum products.
Temperature Range	-20°C to 100°C
Tube	Black NBR blend compound, oil and non-aggressive chemical resistant
Reinforcing	High tensile synthetic yarns
Cover	Smooth finish, NBR/EPDM blend compound, Oil, abrasion and weather resistant
Special Features	Black, Blue, Yellow, Red, Green covers allow for color coding where cross contamination of media can affect the safe operation of plant equipment. UV stabilized; Oil mist resistant, Non Conductive. General tolerances acc to ISO 1307

## BLACK

Part no.	Dimensions			Working Pressure		Safety Factor	Bend radius	Weight	Length
	Inch	ID (mm)	OD (mm)	psi	Bar				
AMP200615N	1/4"	6,4	14,0	300	20	4:1	40	0,24	100
AMP200816N	5/16"	7,9	16,0	300	20	4:1	50	0,25	100
AMP201018N	3/8"	9,5	18,0	300	20	4:1	60	0,27	100
AMP201221N	1/2"	12,7	20,0	300	20	4:1	75	0,38	100
AMP201930N	3/4"	19,0	29,0	300	20	4:1	110	0,63	100
AMP202537N	1"	25,4	36,0	300	20	4:1	150	0,96	100
AMP203245N	1-1/4"	31,8	45,0	300	20	4:1	190	1,24	100
AMP203854N	1-1/2"	38,1	54,0	300	20	4:1	225	1,44	100

## BLUE

Part no.	Dimensions			Working Pressure		Safety Factor	Bend radius	Weight	Length
	Inch	ID (mm)	OD (mm)	psi	Bar				
BMP200615B	1/4"	6,4	14,0	300	20	4:1	40	0,24	100
BMP200816B	5/16"	7,9	16,0	300	20	4:1	50	0,25	100
BMP201018B	3/8"	9,5	18,0	300	20	4:1	60	0,27	100
BMP201221B	1/2"	12,7	20,0	300	20	4:1	75	0,38	100
BMP201930B	3/4"	19,0	29,0	300	20	4:1	110	0,63	100
BMP202537B	1"	25,4	36,0	300	20	4:1	150	0,96	100
BMP203245B	1-1/4"	31,8	45,0	300	20	4:1	190	1,24	100
BMP203854B	1-1/2"	38,1	54,0	300	20	4:1	225	1,44	100

## YELLOW

Part no.	Dimensions			Working Pressure		Safety Factor	Bend radius	Weight	Length
	Inch	ID (mm)	OD (mm)	psi	Bar				
CMP200615Y	1/4"	6,4	14,0	300	20	4:1	40	0,24	100
CMP200816Y	5/16"	7,9	16,0	300	20	4:1	50	0,25	100
CMP201018Y	3/8"	9,5	18,0	300	20	4:1	60	0,27	100
CMP201221Y	1/2"	12,7	20,0	300	20	4:1	75	0,38	100
CMP201930Y	3/4"	19,0	29,0	300	20	4:1	110	0,63	100
CMP202537Y	1"	25,4	36,0	300	20	4:1	150	0,96	100
CMP203245Y	1-1/4"	31,8	45,0	300	20	4:1	190	1,24	100
CMP203854Y	1-1/2"	38,1	54,0	300	20	4:1	225	1,44	100

## RED

Part no.	Dimensions			Working Pressure		Safety Factor	Bend radius	Weight	Length
	Inch	ID (mm)	OD (mm)	psi	Bar				
DMP200615R	1/4"	6,4	14,0	300	20	4:1	40	0,24	100
DMP200816R	5/16"	7,9	16,0	300	20	4:1	50	0,25	100
DMP201018R	3/8"	9,5	18,0	300	20	4:1	60	0,27	100
DMP201221R	1/2"	12,7	20,0	300	20	4:1	75	0,38	100
DMP201930R	3/4"	19,0	29,0	300	20	4:1	110	0,63	100
DMP202537R	1"	25,4	36,0	300	20	4:1	150	0,96	100
DMP203245R	1-1/4"	31,8	45,0	300	20	4:1	190	1,24	100
DMP203854R	1-1/2"	38,1	54,0	300	20	4:1	225	1,44	100

## GREEN

Part no.	Dimensions			Working Pressure		Safety Factor	Bend radius	Weight	Length
	Inch	ID (mm)	OD (mm)	psi	Bar				
EMP200615G	1/4"	6,4	14,0	300	20	4:1	40	0,24	100
EMP200816G	5/16"	7,9	16,0	300	20	4:1	50	0,25	100
EMP201018G	3/8"	9,5	18,0	300	20	4:1	60	0,27	100
EMP201221G	1/2"	12,7	20,0	300	20	4:1	75	0,38	100
EMP201930G	3/4"	19,0	29,0	300	20	4:1	110	0,63	100
EMP202537G	1"	25,4	36,0	300	20	4:1	150	0,96	100
EMP203245G	1-1/4"	31,8	45,0	300	20	4:1	190	1,24	100
EMP203854G	1-1/2"	38,1	54,0	300	20	4:1	225	1,44	100

## MATEC GROUP SRL

VIA I MAGGIO, 7 - PESCHIERA BORROMEO (MILANO) - ITALIA

Tel. +39 02 55 30 17 88 - Fax +39 02 54 72 158

matec@matecgroup.com - www.matecgroup.com